# **TM12**

### SELF-PROPELLED TELESCOPIC MAST LIFT



- Industry-leading self-propelled telescopic mast lift
- Versatile, robust and simple to use
- Drives through a standard doorway
- 0.5m roll-out extension deck
- Ideal for many applications from construction to stockpicking!



### SELF-PROPELLED TELESCOPIC MAST LIFT

## **TM12**


DIMENSIONS	TM12
Max. working height	5.6m
Max. platform height ( <b>A</b> )	3.6m
Platform size (stowed)	0.74m x 0.96m
Platform size (extended) ( <b>E</b> )	0.74m x 1.46m
Extension deck length	0.5m
Overall width ( <b>B</b> )	0.76m
Overall length ( <b>D</b> )	1.34m
Stowed height ( <b>C</b> )	1.62m
Ground clearance	76mm


PERFORMANCE	
Platform capacity (SWL)	227kg
Max. drive height	3.6m
Max. wind speed	12.5m/s
Max. drive speed (stowed)	3.2km/h
Max. drive speed (elevated)	0.43km/h
Raise/lower time	16/19 sec
Gradeability	25%
Max. operating slope (side to side	2°
Max. operating slope (front to back	ck) 2°
Inside turning radius	0.36m
Outside turning radius	1.55m
Tyres	279mm non-marking rubber
Parking brake	2 wheel, spring-applied, hydraulically-released with manual overdrive
Drive system	dual front hydraulic motors
Controls	proportional

POWER	
Power source	24V 4hp DC electric motor 4-220 Ah batteries
Battery charger	18 amp

WEIGHT
Weight 910kg

### TURNING RADIUS





#### STANDARD FEATURES

- Roll-out deck extension
- Hydraulically powered descent
- Proportional controls
- Saloon-door style entry gates
- Descent and tilt alarms
- Emergency lowering at chassis controls
- Non-marking rubber tyres
- Crane lift points
- Horn
- 2 persons indoor
- 1 person outdoor
- Selectable motion alarm
- Integrated battery charger 90V-240V 25A
- Hour meter & on-board diagnostics display
- 2 year parts & labour, 5 year structural warranty
- CE approved

#### **OPTIONS**

- Special paint colours
- Environmental hydraulic oil



Vigo Centre, Birtley Road, Washington, Tyne & Wear, NE38 9DA, U.K.

t: +44 (0) 845 1550 057 e: sales.emea@snorkellifts.com